

AD-A167 945


TASK AND TRAINING REQUIREMENTS ANALYSIS FOR ADVANCED ARMY HELICOPTERS: Final Summary Report

Arthur I. Siegel, Edward G. Madden, and Mark G. Pfeiffer Applied Psychological Services, Inc.

for

ARI Field Unit at Fort Rucker, Alabama Charles A. Gainer, Chief

TRAINING RESEARCH LABORATORY Seward Smith, Acting Director





U. S. Army

Research Institute for the Behavioral and Social Sciences

December 1985

Approved for public release; distribution unlimited.

86 5 19 014

BLANK PAGES IN THIS DOCUMENT WERE NOT FILMED

U. S. ARMY RESEARCH INSTITUTE FOR THE BEHAVIORAL AND SOCIAL SCIENCES

A Field Operating Agency under the Jurisdiction of the Deputy Chief of Staff for Personnel

EDGAR M. JOHNSON Technical Director WM. DARRYL HENDERSON COL, IN Commanding



A-1:

This report, as submitted by the contractor, has been cleared for release to Defense Technical Information Center (DTIC) to comply with regulatory requirements. It has been given no primary distribution other than to DTIC and will be available only through DTIC or other reference services such as the National Technical Information Service (NTIS). The vicws, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation.

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
	3. RECIPIENT'S CATALOG NUMBER
ARI Research Note 85-105 AD - A1679	72
4. TITLE (and Subility) TASK AND TRAINING REQUIREMENTS ANALYSIS	s. Type of Report & Period Covered Final Report
FOR ADVANCED ARMY HELICOPTERS:	July 81 - April 83
Final Summary Report	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(s)
Arthur I. Siegel, Edward G. Madden,	MDA 903-81-C-0439
and Mark G. Pfeiffer	
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Applied Psychological Services, Inc.	i
Science Center,	2Q263739A793
Wayne, PA 19087	12. REPORT DATE
Army Research Institute Field Unit at Fort Rucker.	December 1985
Alabama, PERI-SR,	13. NUMBER OF PAGES
Fort Rucker, AL 36362 14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS. (of this report)
U.S. Army Research Institute for the Behavioral	Unclassified
and Social Sciences, 5001 Eisenhower Avenue,	}
Alexandria, VA 22333-5600	18a. DECLASSIFICATION/DOWNGRADING
16. DISTRIBUTION STATEMENT (of this Report)	ln/a
Approved for public release; distribution unlimited	
]	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different from	en Report)
18. SUPPLEMENTARY NOTES	
Charles A. Gainer, contracting officer's representat	tive
Currends:	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number, Training Function Allocation Cre	w Workload
Training Requirements, System Analysis Cre	w Integration.
Simulacion, reall real real real real real real rea	•
Task Analysis, AHIP Human Factors, Helicopter Design,	
20. ABSTRACT (Continue on reverse aids if recessary and identify by black number)	
A series of interrelated analytical tasks was com	pleted in order to support the
training development of the AHIP scout, AH-64, and A	H-IS(MC) helicopters. The
tasks were: (1) mission profile analysis, (2) time s of functions, (4) detailed task analysis, and (5) tr	eries analysis, (3) allocation aining requirements develon-
ment.	- '
Each task resulted in an individual set of end pr	oducts which provide required
information in themselves and which formed the basis	of later tasks. (over)

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

Research Note 85-105

20. Abstract (continued)

The need for coordination training, both within helicopter team training courses and between team training courses, and for training in problem solving are pointed out, along with the possible need for selection standards methods which are based on the crew members' ability to solve problems while under high levels of collateral perceptual-motor load.

FLD 19

CONTRACTOR CONTRACTOR

REPORT DOCUMENTATION	PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(a)	·	8. CONTRACT OR GRANT NUMBER(a)
9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
·		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS(II differen	t from Controlling Office)	15. SECURITY CLASS. (of this report)
•		
·		15. DES. ASSISTED AND COMMENTATION
	-	154. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)		
		·
17. DISTRIBUTION STATEMENT (of the abstract entered	in Block 20, If different fro	en Report)
18. SUPPLEMENTARY NOTES		
- -		
19. KEY WORDS (Continue on reverse side if necessary an	d identify by block number)	
20	d Identify by black	
20. ABSTRACT (Continue on reverse side if recessary and	a restaily by block number)	Į
		·

TABLE OF CONTENTS

I.	INTRODUCTION	Page
••	MTHODUCTION	1
II.	METHOD	2
	Task 1Mission Profiles	2
	Task 2 Time Series Analyses	3
	Task 3Allocation of Functions	6
	· · · · · · · · · · · · · · · · · · ·	9
	Task 5Training Requirements Specification	14
	System Description	21
	Instructor Station	23
	Audio-Visual Subsystem	24
	Trainee Stations	24
	Adaptability	24
	Deviation of ITTS from High Fidelity Simulation	24
	Adequacy of the ITTS	26
III.	DISCUSSION	27
	Intellective Load	27
	Other Implications · · · · · · · · · · · · · · · · · · ·	
Ref	ferences	31
App	pendix A Mission Profiles	33
App	pendix B Example of Results of Time Series Analyses	41
App	pendix C Highly Scaled Intellective Categories for Crew Members in Each Helicopter Type	51

LIST OF TABLES

$\frac{\mathrm{T}}{\mathrm{T}}$	<u>able</u>		Page
	1	Flight Segments Contained in Each Mission	• 7
	2	Frequency of Moderate to High Loads* Before and After Optimum Allocation and Percentage Reduction ($\Delta\%$)	10
	3	Frequency of Most Heavily Demanded Intellective Operations Across Functions for Each Helicopter Type	15
	4	Preferred Type of Training for Each Learning Type	17
	5	AHIP Transition Training Summary	18
	6	AH-64 Transition Training Summary	19
	7	AH-1S(MC) Transition Training Summary	20
	C-1	Most Highly Scaled Intellective Categories Involved in Functions of AHIP Helicopter Pilots	53
	C-2	Most Highly Scaled Intellective Categories Involved in Functions of AHIP Helicopter Observers	54
	C-3	Most Highly Scaled Intellective Categories Involved in Functions of AH-64 Helicopter Pilots	55
	C-4	Most Highly Scaled Intellective Categories Involved in Functions of AH-64 Helicopter Copilots	57
	C-5	Most Highly Scaled Intellective Categories Involved in Functions of AH-1S Helicopter Pilots	• 58
	C-6	Most Highly Scaled Intellective Categories Involved in Functions of AH-1S Helicopter Copilots	· 6 0

LIST OF FIGURES

Figure	
1	Flow of program information
2	An example of the first half of the task analysis worksheet 11
3	Schematic of integrated transition training system 22
4	Individual trainee station showing modular unit interfaces (MUI)25
A-1	Mission analysis results for AHIP/AH-64 attack mission35
A-2	Mission analysis results for AHIP/AH-1S(MC) engage predesignated target mission
A-3	Mission analysis results for AHIP/AH-64 reconnaissance screening mission
A-4	Mission analysis results for AHIP/AH-1S(MC) reconnaissance screening mission
A-5	Mission analysis results for AHIP/FAAO mission39
B-1	An example of the results of the time series analysis43

I. INTRODUCTION

Army helicopter employment, in the past decade, has been the subject of considerable change including increased emphasis on terrain flight, multiaircraft teams, flight during marginal weather conditions, and night operations. Hand-in-glove with the doctrinal changes are substantial modifications in flight, avionics, and weapon systems. The equipment system changes, driven by the advanced doctrinal emphasis, are necessary in order to meet the demands of new missions and tactics.

The combination and interaction of doctrinal changes and new equipment systems has direct implications for training. Demands for new skills and knowledges have been created. There have also been corresponding increases in the operator's loads, both intellective and perceptual-motor.

The development of an effective manning system for the advanced helicopters requires a thorough front-end analysis designed to provide timely information on task functions, crew/team coordination requirements, intellective requirements, and training requirements.

To this end, a series of interrelated tasks was performed: (1) scenario development and mission profile analysis (Applied Psychological Services, 1982a), (2) time series analysis (Applied Psychological Services, 1982b,c,d), (3) allocation of functions (Applied Psychological Services, 1982e), (4) detailed task analyses for the AHIP scout helicopter, the AH-64, and the AH-1S(MC), (Applied Psychological Services, 1982f,g,h) and (5) training requirements development (Madden, Pfeiffer, and Siegel, 1983).

The details of each of the study tasks are presented in the individually referenced reports. The present report summarizes the total program.

The analysis which led to the individual requirements for advanced combat missions in emerging Army helicopters proceeded in an orderly fashion. The entire undertaking was organized according to principles derived from general systems theory. The various tasks represented successive stages in the systematic development of program information. The general flow of work across tasks is illustrated in Figure 1. As indicated in Figure 1, the output from each task served as the input into the next task(s). In this way, program information developed at each stage formed the basis for the analyses at the next stage. The final box of Figure 1, "evaluation," was not considered within the present work. It is included in the figure to suggest the feedback loop essential to any front-end analysis.

II. METHOD

A summary of the details of the methods and results of each step of the work is presented categorically below.

Task 1--Mission Profiles

An analysis of the operational requirements is the necessary starting point for a system analysis. During Task 1, mission profile development, the missions and systems lists employed in later study steps were identified for the AHIP, the AH-64, and the AII-1S(MC). To select missions appropriate to current and projected Army operations and tactics, a generalized scenario was developed. Based on the scenario, five missions were identified as a basis for subsequent analyses:

AHIP in conjunction with an AH-64 on an attack against a predesignated target

AHIP in conjunction with an AII-1S(MC) on an attack against a predesignated target

AHIP in conjunction with an AH-64 on a reconnaissance/screening mission

AHIP in conjunction with an AH-1S(MC) on a reconnaissance/screening mission

AHIP on an adjust indirect artillery fire mission (FAAO).

For analytical purposes, each mission was divided into phases, (e.g., enroute, reconnaissance, target servicing) and the phases were divided into meaningful segments (e.g., low level flight, contour flight, evade threat fire).

The equipment systems used by the crew members to perform the various mission activities were identified using the specifications for each helicopter. Eleven systems were analytically differentiated for each aircraft. The exact collection and specific types of equipment varied across aircraft but each equipment system in one helicopter generally had a functional equivalent in the other helicopters. The systems were:

- 1. flight control system
- 2. flight instruments
- 3. external visual field
- 4. integrated flight information system
- 5. systems instruments
- 6. internal communication system

- 7. external communication system
- 8. navigation system
- 9. survivability devices
- 10. sighting devices
- 11. target engagement devices.

The actual mission profile analyses consisted of assessing changes in equipment system use across the phases and segments of each mission. The analyses included identification of equipment systems employed, time (duration) of use, and demand placed on the user during use for each helicopter/mission/phase/segment. The analyses yielded five mission profile analyses. These are presented in Appendix A as Figures A-1 through A-5. The profiles were of sufficient detail to allow subsequent identification of all equipment related tasks, temporal sequences, and overlaps among tasks.

Task 2--Time Series Analyses

The Task 2 time series analyses were concerned with identifying and describing the activities performed in each mission segment. The analyses were executed within the framework of the mission/phases/segments systems established in Task 1. Accordingly, the mission profile analytic data were the inputs into the Task 2 time series analyses.

The activities of crew members in each aircraft were analyzed to assess: (1) the inputs from each equipment system needed to drive the activities, (2) the required outputs, and (3) the operator-equipment functional interactions. Within the transformations of inputs into outputs, the type of information (qualitative, quantitative, or check) processed and the amount and the difficulty of the processing were identified.

Describing and specifying the functional interactions was achieved at the equipment subsystem level. Each equipment system, identified in the Task 1 analysis, was broken into its component subsystems, e.g., one component of the navigation system in the attack aircraft was the doppler display and controls. Describing the task(s) associated with each subsystem in each mission segment specified the operator-equipment functional interaction.

During the course of the analysis, the "criticality" of each operator activity and the "delay tolerance" of the activity were also scaled. The result was a detailed compilation for each operator activity in each aircraft/mission/segment of:

- 1. equipment systems and subsystems involved
- location of each subsystem (P = pilot's station, C = copilot's or observer's station,
 B = both stations)

- 3. the purpose of the operator functional interaction with each subsystem
- 4. who interacts with each subsystem (P = pilot, C = copilot or observer, B = both)
- 5. the type of operator activity (M = motor, V = visual, A = auditory, S = speech)
- 6. the type of information processed (QT = quantitative, QA = qualitative, CK = check)
- 7. the amount and the difficulty of the mental activity involved in completing the operator activity (each scaled from 1 to 7)

Properties Sections equations absorbed regulation

- 8. the amount and the difficulty of the motor activity involved in completing the operator activity (each scaled from 1 to 7)
- 9. the delay tolerance for the operator activity (each scaled from 1 to 5)
- 10. the criticality of the operator activity (each scaled from 1 to 5)
- 11. comments primarily in terms of activity sequence, which elaborated or qualified the information presented.

Items 7, 8, 9, and 10 above, were assessed for both night and day operations.

The analyses were completed by a team composed of a human factors psychologist with military flight experience, an experimental psychologist, a pilot with experience in attack helicopters, and a pilot currently rated in scout helicopters. Inter-rater agreement was attained by requiring that all judgements/assessments/classifications made by a psychologist be reviewed by a helicopter pilot, and that all those made by helicopter pilots be reviewed by a psychologist. Any discrepancies between the initial analyst and the reviewer were resolved in a meeting of the entire team.*

Accordingly, Task 2 elaborated on the mission profiles to provide statements of the tasks performed by each crew member during each segment of the Task 1 analyses along with an analysis of each task.

Figure B-1 in Appendix B shows a sample of the results. While the format of these analyses was very much the same for all three aircraft under study, the systems varied.

^{*} This team completed all of the analyses of the series described throughout this report.




Figure 1. Flow of program information.

Task 3--Allocation of Functions

The results of Task 2 led to an examination of the division of labor across crew members within the three helicopters and of the demands placed on them by the equipment subsystems. In Task 3, an analysis was completed with an emphasis on reducing the load on all crew members, and on equalizing the load across crew members. The missions and segments included in these analyses are presented in Table 1.

The crew member functions used in the allocation of function analyses were derived from the Task 1 analyses. This involved specifying the functional use of each system, e.g., system 1, flight control, became function 1, control flight with cyclic, collective, and pedals. The derivation of the functions was performed for each aircraft so that differences in equipment subsystems among aircraft was reflected in differences in functions. Eleven functions were derived for each aircraft.

THE PROPERTY OF THE PROPERTY O

The analysis progressed in two steps: (1) allocation between crew and equipment, and (2) allocation between crew members of tasks not allocated to the equipment. In each step, a set of rules was rationally applied across aircrafts, missions, and segments.

Throughout both parts of the function allocation, the analysis was at the level of the selected segment by function. Thus, the same function could be assigned differentially between various segments and missions.

To derive the allocation rules, available literature (e.g., Hutchingson, 1981; DeGreene, 1970; Lyman and Fogel, 1961) was consulted to provide an initial set of concepts for allocation of functions to either the equipment or the operator in a system. This conceptualization was extended, adapted, and integrated into a set of rules for the allocation of functions between crew members and equipment:

- 1. Where the process is dependent upon maximum flexibility, assign it to the aircrew; e.g., NOE flight.
- 2. Where the process is dependent upon complex procedures requiring a large number of differentiations or integrations, assign it to the equipment; e.g., estimating target coordinates.
- 3. Where the process is dependent upon infallible memory with its precise source accurately tagged (and ignoring display potential), assign it to the equipment; e.g., weapons available/expended.
- 4. Where the activity involves the consideration of a situational context in which the weightings of the factors involved vary in accordance with the context, assign it to the aircrew; e.g., selecting priority targets.

Table 1

Flight Segments Contained in Each Mission

Segments			Missi	on	
	<u>a</u> *	<u>b</u>	<u>c</u>	<u>d</u>	<u>e</u>
Takeoff	x	x	x	x	x
Enroute/Return					
Low Level	x	x	x	x	x
Contour	×	x	x	x	x
NOE	x	x	x	x	x
Traveling			x	x	
Overwatch	x	x	x	x	
Bounding Overwatch			x	x	
Coordinate Tactical Instrument Plan			x	x	
Tactical Instruments Enroute			x	x	
Precision Approach Radar			x	x	
Enemy Engagement					
Locate/Identify Threats	x	x	x	x	x
Select Fire Position/NOE	x	x	x	x	
Handoff Point Weapon	x	x	x	x	
Handoff Artillery					x
Adjust Fire/Security	x	x	x	x	
Reposition	x	x	x	x	
Mask/Unmask		x		×	x
Engage Target	x	x	x	x	
Assess Damage	x	x			x
Evade Threat Radar/Fire			x	x	
Landing	x	×	x	x	x
Refuel (Hot)/Rearm	x	x	x	x	x

a = AHIP/AH-64 attack

b = AHIP/AH-1S(MC) attack

c = AHIP/AH-64 reconnaissance/screening

d = AHIP/AH-1S(MC) reconnaissance/screening

e = AHIP/indirect fire (FAAO)

- 5. Where the activity involves contextless deductive reasoning, assign it to the equipment; e.g., predicting altitude.
- 6. Where the activity involves inductive reasoning of a straightforward nature, assign it to the equipment; e.g., time to target.
- 7. Where the activity couples active hypothesis formulation with inductive reasoning, assign it to the aircrew; e.g., selecting priority targets.
- 8. Where the activity involves prediction of the future and if the weightings of the variables involved are known, assign it to equipment; e.g., navigation.
- 9. Where the activity is a low probability event not feasible for automation because of the number of possible events, assign it to the aircrew; e.g., selecting evasive route.
- 10. Where the process is dependent on very low absolute threshold sensitivity, assign it to the aircrew; e.g., detecting targets in noise.

CONTRACTOR INCREMENT INCREMENT INCREMENT INCREMENT MANAGEMENT SOUTHER SYNTHE INCREMENT INCREMENT INCREMENT INCREMENT.

11. When the process depends on precise tracking over limited error ranges for extended duration, assign it to equipment; e.g., target tracking.

In some cases, it was believed possible to modify extant equipment or to develop new equipment to achieve the allocation. Examples of such equipment modifications or developments are: (1) data or message sending device, (2) hover hold device, (3) auto pilot, (4) electrocutaneous warning device, and (5) night vision device (improved). In such cases and if the rules so indicated, the function was allocated to equipment.

Once functions were assigned to the aircrew, a second set of rules was used to allocate them to the pilot or copilot/gunner or observer:

- 1. Allocate associated functions to the same crew member.
- 2. Allocate "command" functions to the pilot.
- 3. Make allocations on an optimal allocation basis and not necessarily on a current practice basis.
- 4. Assign integration and coordination functions to the pilot.

- 5. Minimize instances of overloading either crew member.
- 6. Avoid unnecessary fatigue of either crew member.

In making the final between crew member allocations, the intellective and the perceptual-motor load estimates derived during the performance of Task 2 were used to assess the reasonableness of the suggested assignments and reassignments.

As a result, Task 3 provided statements about whether or not each action in the time series analyses of Task 2 is best performed by the aircrew or the equipment and, if allocated to the aircrew, which crew member. The consequences of the optimum allocation are summarized in Table 2. The table indicates that load reductions ranging between 40 and 50 percent are possible by mere reallocation.

Task 4--Task Analysis

In Task 4, detailed task analyses were completed. Each task identified in the Task 2 time series analysis was analyzed to the level of the activity (structurally task, subtask, activity). The analyses decomposed every task performed by the pilot and or copilot/gunner or observer to a detailed level of analyses. The results of the task analyses were used in Task 5 for deriving criterion referenced training objectives, determining training device requirements, developing performance evaluation methods, and for projecting the success potential of trainees on various tasks. Figure 2 presents examples of the task analytic materials. The format of these analyses was very much the same for all three of the helicopters under study. Each compendium presented for each major task:

- ° a list of subtasks involved in completing each task
- ° a list of the activities involved in completing the subtasks
- o for each activity:

displays/controls used indication of response adequacy effect of error quantitative scaling of error impact type of intellective activity involved

Table 2

ASSOCIATE AND SECTION OF THE PROPERTY AND ASSOCIATE ASSOCIATE ASSOCIATE ASSOCIATE ASSOCIATE ASSOCIATE ASSOCIATE

Frequency of Moderate to High Loads* Before and After Optimum Allocation and Percentage Reduction (Δz)

	Δ_x^2	77	39				
FAAO	After	59 42	67				
	Before	101	80				
ce	V V	41	42	97	87	45	77
connaissan	Before After	71	52	89	72	84	75
Re	Before	121	88	166	138	153	134
	<u>7</u>	43	77	20	51	45	42
Attack	After	89	52	74	79	76	77
	Before	Pilot 120	Observer 93	Pilot 148	Copilot 131	Pilot 139	(C) Copilot 132
		AHIP		79-04	40 LIV	٠	AH-1S(MC) C

*Loads scaled 4, 5, 6, or 7

10

F. 1.

1.5.5

Page 1-a of 4	
Function Name Control Flight with Cyclic, Collective, and Pedals	Tack Name FLY LOW LEVEL, VMC
Function No. 1.0	Task No. 1A. 1

TASK ANEXSIS

the resolution continues becauses management streets resolution in the

1021 1022 1021

Ş

			}}			1	
!	ERROR	IMPACT	4	2	ಣ	င	8
	าชส	POTENTIAL	Damage aircraft	Poor effi- ciency of aircraft	Miss desti- nation	Expose aircraft	Poor effi- ciency of aircraft
	RESPONSE	ADEQUACY INDICATION	Visual feedback	Airspeed 10 KIAS	Arrive at predetermined check-points 2 minutes of ETA	Altitude 25 feet	Ball within limits
VMC		DISPLAY(S)/ CONTROL(S)	External visual	Cyclic, collective, pedals	Cyclic	Collective	Pedals
FLY LOW LEVEL,	ACTIVITIES		Route orienta- tion	Hold airspeed	Follow desired course	Hold altitude	Hold trim
Task Name	COPILOT'S SUBTASK	AND NUMBER					
Task No. 1A. 1	PILOT'S SUBTASK	AND NUMBER	1A, 1.1 Control aircraft				
			- Marien den 1 Marie (1964)	11			

PRINT CASSISSI PARADARA GRADINA NO LLO ANDRONA

OPERATIONS OPERATIONS C M CP E U C! R T I was X X X (()	Function No.	ction No	, ,	1.0 1A.1		٥	Ouite	unct	Function Name	Name Name FLY	'''	tro:	Flight with	with VM	Cyclic, C	Collective,	and	Pedals	Page	1-b of 4
X 2 1 2 1 1 1 2 1 1 2 2		NTS SW	7 1 1 101	2 PERAT	SHOUS		m D	PROC	NUCTS	INE L		S S S COUNT CALE	DIFFICULTY	1		PTUAL MO SCRIE VALUE(0)	FREEPTVAL MOTORIDAD VALUENX ED	TIME (SEC)	TRAINING REQUITEMENT	
2 4 estimates 2 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Ì		×						×			3 3	1 (1)	2 (3)						
2 4 4															1	-1	-			visibility load estimates
4	1														8	87	4			
1 1	ļ														8	87	4			
				•											1	1				

quantitative scaling of amount of intellective effort quantitative scaling of difficulty of intellective effort total intellective load (amount x difficulty) quantitative scaling of amount of perceptual-motor effort quantitative scaling of difficulty of perceptual-motor effort total perceptual motor-load (amount x difficulty) time estimation of the activity's mean duration notes--comments (where applicable)

The assessment of the intellective and the perceptual-motor effort involved in completing each activity was dichotomous. If an activity was considered to be primarily intellective in nature, it was classified as such and assessed for the amount and difficulty of the intellective effort involved. Similarly, activities considered to be primarily perceptual-motor in nature were assessed for the amount and difficulty of the perceptual-motor effort.

All intellectual activity was also classified in terms of the activity's content, operations, and products as originally formulated by Guilford (1967). Content referred to the type of information processed and was categorized as:

- ° Figural (F)
- ^o Symbolic (SY)
- ° Semantic (SM).

Operations referred to the type of intellective activity involved and were classified as:

- o Cognition (C)
- ° Memory (M)
- ° Convergent Production (CP)
- o Evaluation (E).

Products referred to output from the interaction of the operation with the content. Products were categorized as:

- o Unit (U)
- ° Classes (CL)
- ^ Relations (R)
- o Transformations (T)
- o Implications (I).

A major result of this intellective analysis was the identification of the intellective categories most heavily involved in helicopter aircrew functions. Tables C-1 and C-2 (Appendix C) present the most highly scaled intellective categories of AHIP pilots and observers while Tables C-3 through C-6 present the most highly scaled intellective categories of AH-64 and AH-1S(MC) pilots and copilots. The intellective operations most heavily demanded can be seen in Table 3.

Task 5--Training Requirements Specification

Trsk 5, training requirements specification, was organized around the functions defined in Task 3 and utilized the task analytic assessments of Task 4. The Task 5 work was executed in four parts. Initially, transition training requirements were defined for the crew members of each aircraft of concern. Training requirements are statements of what a trainee must be able to do or know as a result of training and there was a one-for-one correspondence between the Task 4 task listings and the description of the training requirements. Second, training requirements that transition trainees would be expected to have "filtered" from eliminated or achieved were previously training objectives, reflecting the degree of consideration. Next. proficiency to be achieved in the transition training and criterion (operationally defined measures of performance) were developed. The final concern of Task 5 was identification of the most appropriate training method for training on the required tasks so that performance will be at the required criterion levels. In this regard, preferred training methodologies were isolated and training sequences were systematically developed.

The following definitions were employed:

Behavior: a global statement of crew member's activity during the performance of a subtask

Training requirement: skills and knowledges crew members must learn

Criterion measure: standards of performance to be used within the training context for assessing student mastery

Enabling knowledge: knowledge necessary prior to training on a particular function

Type of learning: classification of the learning required to achieve a given training requirement (see discussion below)

Training technique: a procedure for implementing the learning type

Fidelity: estimated degree of realism required in any required training device

Table 3

Frequency of Most Heavily Demanded Intellective Operations Across Functions for Each Helicopter Type

Pilot's Intellective		Aircraft	
Operations	AHIP	AH-64	AH-1S(MC)
Evaluation	8	16	19
Cognition	9	10	10
Convergent Production	3	5	5
Memory	2	2	1
Copilot's /observer's Intellective		Aircraft	
Operations	AHIP	AH-64	AH-1S(MC)
Evaluation Cognition Convergent Production Memory	12 5 7 0	16 10 8 0	16 4 6 0
METHOL'S	U	U	U

.

Training time: estimated time for average trainee to achieve mastery relative to a criterion objective

Crew/team coordination requirements: statement of crew or team training requirements.

In order to relate each learning type to the preferred type of training, a systematic set of linkage rules was followed. The linkages are shown in Table 4, in which the different types of learning are shown along with the training type most suitable to each learning type. The learning types presented in the first column of Table 4 are defined below:

Signal learning: recognition of a signal, a condition, or a state

Stimulus-response: performance of a specific action when a given condition or set of conditions occur. This involves recognition of the stimulus situation and demonstration of the appropriate response or set of responses

Chaining: performance of a set or a pattern of alternate actions in response to a given condition or set of conditions

Principle learning: transforming system or equipment data to another form so that it can be applied to a problem or a set of problems

Concept formation: learning why a given condition or set of conditions require a given set of responses

Problem solving: learning to recognize the implications of various courses of action.

The major results of task 5 were training summary tables. One table was composed for each helicopter of concern. Each table listed crew member functions, the original number of tasks within each function, the number of remaining tasks after tasks eliminated from transition training were "filtered," suggested training method, estimated hours for an average trainee to achieve mastery, the optimal training sequence, and a statement of crew/team coordination requirements. Tables 5, 6 and 7 present the training summaries for the AHIP, AH-64, and AH-1S(MC), respectively.

The training is designed to provide an aircrew, skilled in helicopter operation, with the basic knowledge and skill for transitioning into the AHIP, AII-64, or AH-1S(MC). The Task 5 report (Madden, Pfeiffer, & Siegel, 1983) also presented an initial concept of a synthetic trainer which was conceived to support proficiency development in both the

Table 4

Preferred Type of Training for Each Learning Type

Learning Training Type Type

Signal Part Task

Stimulus-Response Part Task/Procedural

Chaining Whole Task/Procedural

Principle Whole Task

Concept Formation Whole Task

Problem Solving Whole Task

Table 5

court topopopy forestern hardered broken with

AHIP Transition Training Summary

Crew/Team Coordination	Low	Low	Moderate	Low	High	Low	High	High	Moderate	Moderate
Training Sequence	က	က	2	87	4	1	ശ	9	တ	10
Hours Pilot	2	8	10	က	15	81	သ	വ	8	87
Training Hours Observer Pilot	0	7	10	0	15	8	ល	ល	73	87
Training Method	Whole task/ procedural	Part task/ procedural	Part task/ procedural	Part task/ procedural	Whole task	Part task/ procedural	Whole task/ procedural	Whole task/ procedural	Whole task/ part task	Whole task/ procedural
Remaining Tasks	9	က	10	9	39	က	10	9	23	
Original No. Remaining of Tasks	6	က	10	9	39	က	12	2	63	1
Function	1. Control Flight with Cyclic, Collective, and Pedals	2. Read/Monitor Secondary Flight Instruments	3. Environmental Orientation	4. Use Tilot's MFD/Controls	5. Use Observer's MFD/ Controls	6. Monitor/Read Systems Instruments	7. Intracrew Communication	8. External Communication	9. Use Survivability Devices	11. Use MLMS Controls

Table 6

AH-64 Transition Training Summary

Function	Original No. of Tasks	Remaining Tasks	Training Method	Training Hours CP/G Pilot	Hours Pilot	Training Sequence	Crew / Feam Coordination
 Control Flight with Cyclic, Collective, and Pedals 	6	9	Whole task/ procedural	62	2	&	Low
2. Read/Monitor Flight, Condition and Warning Instruments	4	4	Part task/ procedural	67	2	8	Low
3. Environmental Orientation	10	10	Part task/ procedural	œ	∞	7	Moderate
 Use Integrated Flight Navi- gation Displays, Maps 	9	ဖ	Part task/ procedural	67	2	က	Low
5. Monitor/Read Systems Instruments	က	က	Part task/ procedural	Ø	7	п	Low
6. Intracrew Communication	14	12	Whole task/ procedural	ശ	ស	က	High
7. External Communication	14	13	Whole task/ procedural	ro	လ	9	High
8. Use Navigation System to Fly a Course	13	13	Whole task	œ	∞	4	High
9. Use Survivability Devices	4	び	Part task/ whole task	ო	က	တ	Moderate
 Use TADS/PNVS Displays for ThreatIdentification, Detection, etc 	26 etc	26	Whole task/ procedural	œ	œ	10	High
 Use Devices and Controls to Select/Engage Target 	-	2	Whole task/ procedural	ശ	ശ	11	High

Table 7

general exercises exercises

respected sympletic secretary engagests because the secretary less secretary

AH-1S(MC) Transition Training Summary

Training Hours Training Crew/Team CP/G Pilot Sequence Coordination	2 2 8 Low	2 2 Low	8 8 7 Moderate	2 2 3 Low	2 2 1 Low	5 5 5 High	5 5 6 High	8 8 4 High	2 2 9 Moderate	6 6 10 Moderate	4 4 11 High
Training Metho 1	Whole task/ procedural	Part task/ procedural	Part task/ procedural	Part task/ procedural	Part task/ procedural	Whole task/ procedural	Whole task/ procedural	Whole task	Whole task/ part task	Whole task/ procedural	Whole task/
Remaining Tasks	9	က	10	ဖ	က	10	14	14	87	11	က
Original No. of Tasks	6	က	10	ဖ	က	12	15	14	64	11	က
Function	 Control Flight with Cyclic, Collective, and Pedals 	2. Read/Monitor Primary Flight Instruments	3. Environmental Orientation	4. Use Integrated Flight Navigation Displays, Maps	5. Read/Monitor Caution, Warn- ing and Sequence Instruments	6. Intracrew Communications	7. External Communications	8. Use Navigations Systems to Fly a Course	9. Use Survivability Devices	10. Use Visual Sighting Devices for Threat Identification, Detection	11. Use Devices and Controls to

7

Y

100 MM 800

system operation and problem solving aspects of helicopter combat mission operations.

The system, called the Integrated Transition Training System (ITTS), and shown in Figure 3, is based on the premise that a trainer which appropriately allows for the inclusion of principles of learning in the training situation will more fully support the training than one of higher fidelity (i.e., a full scale flight simulator) but less amenable to the inclusion of learning principles.

The ITTS possesses at least the following advantages:

- 1. The hardware system can accommodate individual and crew training for the AHIP, AH-64, and AH-1S(MC). Software drives the system so that displays appropriate to each aircraft type can be presented on trainee terminals, depending on the individual/crew to be trained.
- 2. Similarly, the system can be employed to train scout-attack helicopter teams. Such team training is believed essential to the successful completion of a number of missions.
- 3. Training economy is introduced by accommodating up to eight trainees at any one time. Each trainee may be trained at his own pace. Moreover, four crews (eight trainees) may be accommodated simultaneously.
- 4. The synthetic trainer accommodates team training and any mix of aircraft type can be simulated when team training is presented.
- 5. The ITTS can accommodate both procedural training and problem solution training.
- 6. The trainer fully takes advantage of principles of learning such as prompts, feedback of performance adequacy, and adaptive training.

System Description

The ITTS contains four major components, (1) an instructor station, (2) individual trainee stations, (3) audio-visual support media, and (4) computer subsystem. Each major component serves a unique purpose. Direct communication between the various stations is included and various communication links can be enabled or disabled at instructor option.




Figure 3 Schematic of integrated transition training system.

Instructor Station

The instructor station is interactive with direct links to the trained stations, the support computer, relevant data bases, and the audio-visual support system. The instructor's station possesses two terminals and independent keyboards for each. One terminal is used in foreground mode and the other is used for background mode activities. The capability to monitor and interact in both the foreground and the background modes enhances the system's flexibility.

In the foreground mode the instructor can:

- monitor information presented on the trainee terminals
- o select a specific student's display to monitor
- allow input on any selected display to be monitored by selected trainee(s)
- o enter problems and situations for a solution
- o "freeze" action
- o advance a problem or revert back to an earlier point in a scenario
- o modify problems to meet contingencies
- o perform criterion attainment assessments.

This capability allows the instructor to make specific points or develop ideas while, at the same time, standardized training is maintained.

The background mode allows independent assessment of activities including:

- o individual progress toward attaining criterion objectives, i.e., historical data on previous criterion assessments
- each trainee's solution to an ongoing training problem as it is recorded by the trainee
- number of students completing a particular lesson plan
- o progress within any lesson plan
- any outstanding trainees in current lesson (both superior and inferior)
- o each student's progress record.

Accordingly, the background mode allows the instructor to assess the progress of each trainee without disrupting foreground activities. The student progress data base is continuously accessible and updated. Accordingly, the need for individual, crew, or team remedial training can be quickly identified.

Audio-Visual Subsystem

Functionally integrated with the instructor station is the audic-visual support subsystem. This subsystem includes a variety of aids, such as, slide-tape presentation, video disc presentations, slides, and tutorial materials. The mix of audic-visual aids for any lesson plan varies and, at instructor option, may be projected on any one or all of the trainee station screens or on the large video projection screen.

Trainee Stations

A CONTROL OF THE STATE OF THE S

Each of eight trainee stations is interactive and adaptive. Each station contains a CRT, a keyboard, and a set of dedicated keys. Each trainee station is designed to accept a variety of hand and foot controls and these can be integrated as modular units. The controls are specific to the aircraft and the crew station being trained. Such items are included as a cyclic, collective, pedals, and tracking controls. The station is interfaced to accept the modular units. Interfaces can be seen in Figure 10.

Adaptability

One of the more useful aspects of the ITTS is its adaptability to training individuals, crews, and scout-attack teams.

Training in the ITTS for individual tasks is straight forward; the trainees use their own terminals independently. In training for tasks requiring coordination of or coordinated activities between crew members, the arrangement and function are different. The trainees are organized into pairs. One member assumes the role of pilot while the second assumes that of the observer or copilot/gunner. Each trainee station is suitably configured for the aircraft type(s) involved. Early training deals with procedures; later training involves coordinated activity and problem solving. All are accomplished in the same synthetic trainer.

In team training, the same arrangement is used but with some modifications. Two or more groups of trainees are involved—a scout and an attack group. Each crew works in a station configured for their aircraft and their role. Headphones or links through the CRTs enable communication between crew members and team members.

Deviation of ITTS from High Fidelity Simulation

The ITTS is not a high fidelity simulator. Such lack of high fidelity possesses cost advantages. Additionally, high realism in the training situation does not guarantee success on the actual flight task.




Figure 4 Individual trainee station showing modular unit interfaces (MUI).

S

There is not always a high correlation between the degree of realism and the effectiveness of a training system. Intentional deviations from realism may even improve the effectiveness of a training system.

Adequacy of the ITTS

The ITTS concept was subjected to a systematic analysis to determine, in the assessors' (two human factors engineers and a scout helicopter pilot) judgments, the adequacy of the system. To this end, the perceived ability of the system to train all of the tasks subsumed by each helicopter function was analyzed. All of the judgments were assessments of the relationship between the system, the subtasks to be trained, and the various components of adequacy examined.

Adequacy was examined in terms of:

- o scope can the various training requirements be met using the system?
- o training objectives what percentage of each training objective can be expected to be achieved using the system?
- o familiarization is the system adequate for familiarizing the trainees with performance and system limits?
- o understanding does the system adequately enable trainees to understand the tasks, the techniques of system use, and the concepts governing their use?
- o problem solving what is the system's adequacy in the critical area of identifying problems and selecting optimum solutions?

Separate analyses were performed for the AHIP, the AH-64, and the AH-1S(MC).

The analyses indicated that:

- o the system can be anticipated to allow performance criterion attainment for about 80 percent of the set of the transition training requirements
- o the strengths of the ITTS system come mainly from its support of more cognitive areas of flight, such as understanding implications and problem solving

III. DISCUSSION

The aircrew training community has become very sensitive to accidents linked to error in pilot judgment, (e.g., Brecke, 1982, Jensen, 1982). New forms of training have been suggested to foster the development of accurate, rapid decision making in complex, uncertain, and stressful situations in which time is a critical variable.

Similarly, the various analyses summarized earlier in this report repeatedly indicated the requirements for problem analysis and solution and/or crew/team coordination training if mission success is to be attained and crew member safety is to be maintained.

The problem solving and crew coordination emphasis also possesses direct implications for the selection and training of nonaviator observers. The observer training needs to be integrated with the pilot training for tasks requiring intracrew coordination and with attack crews for tasks requiring team coordination. Before crew or team training can be administered, the observers will require some individual training within a curriculum which contains various aviation concepts, e.g., navigation, principles of flight.

It may also be necessary to devise selection criteria other than those applicable to the Armor Reconnaissance Specialist MOS (MOS 19D10 or 19D20) from which observers are to be drawn. Perhaps, observer candidates should be at least partially screened on the basis of the Revised Flight Aptitude Selection Test or some variant of it to ensure aptitude for the aviation environment.

Intellective Load

Another approach to the problem of selecting persons who can perform complex problem solving in the time-sharing situation involves assessing the intellective load carrying capacity of the candidates. Intellective load carrying capacity is a multidimensional concept not directly related to "intelligence," as assessed in most "intelligence tests," or by the Armed Services Vocational Aptitude Battery (ASVAB). The intellective load carrying capacity concept is derived from information theory and a variety of information processing oriented theories (e.g., Broadbent, 1963), which suggest that individual channel capacity is a critical determinent of the adequacy of an individual's response to events and configurations.

Within the human factors field, there is a dearth of data on the effects of intellective channel capacity on performance. Few studies have attempted to assess the effects of increasing intellective loads on an operator's ability to use properly a system or perform perceptual-motor tasks. Siegel and Cosentino (1971) noted that a need exists for a technique which will enable measurement of the intellective load which a given system operator can manage. Within such a technique, it must be possible to vary the intellective load on the operator in a known, controlled, quantifiable manner, while the perceptual-motor load is held constant. Moreover, the task material must be based on and drawn from a sound concept of intellective structure. Finally, the technique must allow precise statement of the effect, if any, of intellective overload on the operator's performance. Such a technique would enable answers to questions such as:

の自分などの対象を行っているのでは、

TOURS AND TOURS PRODUCED PRODUCED CONTROL CONTROL

- o At what intellective load level does this operator's motor performance start to deteriorate?
- What is the effect of various types of intellective loading on this operator's performance?
- Ocan this operator manage a higher load for one type of intellective task than for a second type of intellective task?
- What type of information presented to the operator causes the earliest overload?
- Obose presenting the same information, in a different manner, produce less of an intellective load on the operator?
- o Where in the operator's task sequence does the least intellective load occur?
- o How can the intellective load on the operator be lightened?

The method, developed by Siegel and Cosentino (1971), is based on simultaneous performance of a Thurstone scaled set of intellective tasks and a pursuit tracking task. The point on the intellective scale at which the transfer function changes is assumed to represent the intellective load carrying capacity of the subject. The Siegel and Cosentino scales for the intellective load measurements were based on Guilford's (1967) Structure-of-Intellect model of human intellectual function. Intellective functions relevant to the astronaut tasks were identified and twelve cells of the model's 120 were selected as representative of the mental operations performed most frequently by astronauts.

A set of test items, designed to represent increasing mental load, ranging from easy to difficult, was developed and validated for each cell. Accordingly, each item could be represented along a scale of intellective load.

The pursuit tracking task provided the baseline against which the effects of intellective load could be measured. The tracking target was generated as a function of the sum of four sine waves. It was assumed that within clearly defined limits, tracking is a direct function of the target's input frequencies. Siegel and Cosentino (1971) anticipated that if input signal frequency is held constant, deterioration of amplitude ratio and of phase lag will occur when the intellective load of Guilford defined intellective items reaches elevated difficulty levels as defined by the underlying Thurstone scale of difficulty. The point of deterioration, as indicated by a transfer function change, was taken as indicating the "threshold" of the operator.

The method was tested by Siegel and Williams (1973) who concluded that: the intellective load carrying threshold concept possesses merit, intellective load carrying ability seems to be measurable, and thresholds vary within individuals and across intellective functions as well as across individuals within functions.

The technique seems to represent a useful method for assessing individual differences in intellective load carrying capacity in helicopter crew members and seems to merit consideration for use in this regard.

Other Implications

The major emphasis throughout this report was on the derivation of transition training requirements and methods with secondary emphasis on an Integrated Transition Trainer concept and tertiary emphasis on selection. However, this emphasis is not meant to diminish the need for flight training, refresher training, and advanced training in squadrons and elsewhere. Because the transition training will provide realistic, mission oriented learning and proficiency development, it will allow the helicopter crews and teams to enter into and proceed more rapidly in unit training but by no means can it be expected to substitute for that training.

Similarly, depending on the design of the transition trainer, a need may still exist for a limited number of part task trainers. Use of the mast mounted sight in the AHIP and use of night vision devices may represent examples of areas which might profit from part task trainers or specially designed training situations.

Communication content training represents another area in which pay off can be anticipated both in terms of mission success and promulgation of flight safety. The various analyses indicated a need for coordination (communication) both within crews and within and across teams. Improved communication can be conceived as a force multiplier in much the same way as command and control can be conceived as force multipliers. The emphasis here is on the content of communications and not on how to work various communication devices.

What suggestions should be made? What should be the content of such suggestions? When should information be provided? What information? When and what kind of information should be requested? From whom and how often? Helicopter research in the Navy (Siegel and Federman, 1968) has indicated that "successful" and "unsuccessful" antisubmarine warfare helicopter attacks can be differentiated on the basis of the communication content during the attacks. It seems reasonable to expect that the same result will hold for Army helicopter attack teams.

Finally, although the present report placed its emphasis on training requirements and methods, the need for proper selection-especially in regard to observers, but also for pilots-was suggested. Accordingly, some emphasis was placed on assessing the ability of crew members to process intellective loads while simultaneously performing collateral tasks. It seems that proper and improved selection, coupled with training that meets helicopter training requirements, can advance the capability of the man-equipment integrals considered throughout this report.

ストードでする。そのでは、これには、「Particle Control Control

REFERENCES

- Applied Psychological Services. Mission profiles for near term scout helicopter in association with attack aircraft. Wayne, PA: Applied Psychological Services, March 1982a. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. <u>Time series analysis for the AHIP.</u> Wayne, PA: Applied Psychological Services, July, 1982b. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. <u>Time series analysis for the AH-64</u>. Wayne, PA: Applied Psychological Services, April 1982c. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. <u>Time series analysis for the AH-1S(MC)</u>. Wayne, PA: Applied Psychological Services, June 1982d. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. Function allocation for near term scout helicopter in association with attack aircraft. Wayne, PA: Applied Psychological Services, July 1982e. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. <u>Task analysis for the AHIP</u>. Wayne, PA: Applied Psychological Services, September, 1982f. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. <u>Task analysis for the AH-64.</u> Wayne, PA: Applied Psychological Services, October, 1982g. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Applied Psychological Services. Task analysis for the AH-1S(MC). Wayne, PA: Applied Psychological Services, November, 1982h. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Brecke, F. H. Instructional design for aircrew judgment training. Aviation, Space, and Environmental Medicine, 1982, 53, 951-957.
- Broadbent, D. E. Division of attention and the decision theory of signal detection. Proceedings of the Royal Society, 1963, 158, 222.

- DeGreene, K. B. (Ed.) Systems Psychology. New York: McGraw-Hill, 1970.
- Guilford, J. P. The nature of human intelligence. New York: McGraw-Hill, 1967.
- Huchingson, R.D. <u>New horizons for human factors in design</u>. New York: McGraw-Hill, 1981.
- Jensen, R.S. Selected papers from the first international symposium on aviation psychology: I. Aviation, Space, and Environmental Medicine, 1982, 53, 949-950.
- Lyman, J., & Fogel, L.J. The human component, in E.M. Grabbe, et al. (Eds.) Handbook of automation, computation and control, New York: Wiley, 1961.
- Madden, E.G., Pfeiffer, M.G. & Siegel, A.I. <u>Transition training requirements for crewmembers of advanced/improved Army helicopters.</u>

 Wayne, PA: Applied Psychological Services, January, 1983. (Under Contract No. MDA 903-81-C-0439 with the U.S. Army Research Institute).
- Siegel, A.I., & Federman, P.J. <u>Increasing ASW helicopter effectiveness</u>
 through communications training. Wayne, PA: Applied Psychological Services, October, 1968.
- Siegel, A.I., & Cosentino, J. A technique for measuring the intellective load capacity of system operation. Wayne, PA: Applied Psychological Services, Inc., May 1971.
- Siegel, A.I., & Williams, A.R. <u>Identification and measurement of the</u>
 <u>intellective load carrying capacity</u>. Wayne, PA: Applied Psychological
 <u>Services</u>, 1974.

APPENDIX A

Mission Profiles




Figure A-1. Mission analysis results for AHIP/AH-64 attack mission.




Figure A-2. Mission analysis results for AHIP/AH-1S(MC) engage predesignated target mission.




Figure A-3. Mission analysis results for AHIP/AH-64 reconnaissance screening mission.




Figure A-4. Mission analysis results for AHIP/AH-1S(MC) reconnaissance screening mission.




Figure A-5. Mission analysis results for AHIP/FAAO mission.

APPENDIX B

Example of Results of Time Series Analyses

announced transcreen transcreen transcreen te

Flight Condition: International Interaction and air-tensor Flight Condition: Recentled Automatic. Page Locational Interaction Performance Post	_	Visibility Condition:	D-N VMC	Phase: Target	Servicing				Summary No.:	y No. :	3.1.a.1	- 	Aircra	Aircraft: AH-64
Systems Local tion Poperator Equipment Perform Operator Information Information Population Perform Activity tion Type D/N Amit Diff Amit	P4	Flight Condition:	NOE/C	ONTOUR	1	Segment:	Target Acc	quisiti	on: Reco	orded A	utoma	<u>.</u> 2	Page	7
1. Plight Controls Maintain obstacle clearance P M QA D S 4 4 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 7 6 7 6 7 6 7 </td <td>۱.۰</td> <td>ivsteins</td> <td>Loca- tion</td> <td>Operator-Equipment Functional Interaction</td> <td>Perform- ed by</td> <td>Operator Activity</td> <td>Informa-</td> <td>7/0</td> <td>Mental Amt Di</td> <td>o</td> <td>lotor</td> <td></td> <td></td> <td></td>	۱.۰	ivsteins	Loca- tion	Operator-Equipment Functional Interaction	Perform- ed by	Operator Activity	Informa-	7/0	Mental Amt Di	o	lotor			
a. Cellective B Maintain obstacle cleavance difference P M QA D 5 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 1. Image of the clean and alive strong a	-:	Flight Controls		1 1				Ω		$\overline{}$			Calify	Continents
a. Collective B Maintain obstacle clearance P M QA D 5 4 4 4 5 5 5 5 5 5 1 Image Image Image M QA D 5 5 5 5 5 5 1 2 2 3 4 4 4 4 4 4 4 4 4 4 4 4 4 5	l							z		-				quire target while
b. Cyclic B. Control direction and air-leading and air-leading and air-leading and air-leading and air-leading and air-leading are leading at the state of the s		a, Collective		Maintain obstacle clearance	d	M	٥٩٨	D		┞	-	5	5	masked Sequence
B Control direction and air- P M QA D 5 5 4 4 5<	ı		\downarrow					z	_	-	2	2	5	1. Enable waypoint
c. DASE Control Paperd N 6 5 5		b. Cyclic	<u> </u>	and	a,	M	ďγ	Q		-	4	5	5	target acquisition
c. DASE Control P M QA D A 4 A B Control trim P M QA D 3 4	43		_	speed				z	-	-	ေ	5	r.	to TADS (FCP)
Fourth F	3	c. DASE Control						D	-	_	_			b. set acquisition
B Control trim P M QA D 3 4 <	I	Panel	<u>م</u>					z	-	_	_			Cal
The state of the s		d. Pedals	m	Control trim	Ы	M	QA	Ω	-	├	4	4	5	waypoint target
P N N 3. Sla P N N 3. Sla FC N N FC FC N N FC F B N N FC F B N N F F B N N D D F B N N N D D	I							z	\vdash	_	4	4	2	a, set DEK con-
B	~;	Primary Flight In-						Ω	-	-	_			trol to TRGT b. enter index
B	1	struments						z	_	_	_			storage num-
B B B B B B B B B B B B B B B B B B B		a. Accelerometer	<u>a</u>					Ω		-	_			
	1		\downarrow					Z	_	_	_			FCC
P P P P P P P P P P P P P P P P P P P		b. Airspeed Indica-						D	_					a. press (IPI)T button
Β	l	tor	; 					z			_			
2		c. Attitude Indicator						Q			_			lefthandgrip
	-		_					z						

Figure B-1. An example of the results of the time series analysis.

Visibility Condition:	D-N VMC	Phase:	Target Servicing				Summary No. :	y No. :	3. l. a. 1	- -	Aircraft:	ft: AH-64
Flight Condition:	NOE/C	NOE/CONTOUR	1	Segment:	Target Acquisition: Recorded Automatic,	uísitio	n: Reco	rded A	utomati	ن ا	Page	2 20
				•	Point Target	et					} •	
Systems	Loca- tion	Operator-Equipment Functional Interaction	Perform- ed by	Operator Activity	Informa- tion Type	D/N	Mental Amt Diff	- i -	Motor Amt i Diff	Delay Toler-	Task Criti-	
d. Barometric Alti-	B					Ω		_		331111	(aurea)	Comments
meter	_					z		_				4. Make visual sur-
c. Instantaneous	_ 					Ω			_			vey of TADS dis- play, make small
Vertical Speed						Z		_				adjustments as
f. Standby Compass	<u>a</u>					Д		_	_			required 5. When detected,
						z		-				center target on
7 g. Rader Altimeter	23					a	-	\vdash	_			TAT (CP-G's left
Display						z	-	-	_			handgrip)
h. Master Caution	В	Monitor	В	Λ	CK	Ω	2 2	2	2	6	3	
and Warning Panel						Z	2 2	2	2	6	3	
i. Advisory Caution	М					D						
and Warning Panel						Z			L			
3. External Visual Field	_ 	Monitor surroundings,	щ	V, M	QA	Ω	4 5	4	4	ည	5	
		and flight path			CK	Z	9 9	2	2	2	2	
4. Integrated Flight/						Ω			_			
Navigation Displays						z			_			
a. Electronic Attitude						D						
Director Indicator						z						
b, Horizontal Situa-	<u>a</u>					Ω						
tion Indicator						z						
				Figure	Figure B-1. (cont.	cont.						

Seed assessed to seed assessed

Figure B-1. (cont.)

Visibility Condition: L	D-N VMC	Phase: Target	Servicing			0 4	Summa	Summary No.:	3.1.a.1	a. 1	Aircraft:	t: Alf-64
Flight Condition:	NOF/CC	NOF/CONTOUR		Segment:	Target Acquisition: Recorded Automatic. Point Target	uisitic et	n: Rec	orded	Automa	tic.	Page	3 of 7 Pages
	Loca-	_	Perform-				Mental	- اة	Motor		Task Criti-	,
	tion	Functional Interaction	ed by	Activity	tion Type	Z a	Amt Duff		Amt Diff	ance	cality	Comments
c. Radio Magnetic Indicator	U					z			-	_		
						Ω						
Systems mentaments						z			_			
Emergency Hy-	٢					Ω		-	-			
urduite Fressure Gauge	4				٠	Z			-			
		Check limits	۵	Λ	νტ	Ω	e i	2	2 2	_د	3	
b. Fuel Control	q		•			z	8	2	2 2	3	9	
Final Quantity		Check limits	a	Λ	φĄ	Ω	3	2	2 2	က	3	
Indicator	q					z	3	2	2 2	8	3	
Gas Generator	۵	Check limits	a	Λ	φA	Q	3	2	2 2	3	3	
Indicator	•		•			z	8	2	2 2	3	3	
Oil Pressure In-	۵	Check limits	ď	Λ	Vδ	D	3	2	2 2	3	6	
dicator						Z	3	2	2 2	3	3	
Oil Temperature	۵	Check limits	Ь	Λ	QA	α	3	2	2 2	3	3	
Indicator						Z	3	2	2 2	3	3	
Power Turbine and Main Rotor	8	Check limits	ď	Λ	QA	D	3	2	2 2	3	3	
Speed Indicator						z	3	2	2 2	3	3	
h. Torque Indicator	В	Check limits	<u>م</u>	Λ	QA	D	3	2	2 2	3	3	
						Z	3	2	2 2	3	3	

Figure B-1. (cont.)

Visibility Condition: D	D-N VMC	AC Phase: Target Servicing	ervicing				Summ	Summary No. :	ا :	3.1.a.1	 1	Aircraí	Aircraft: All-64	
Flight Condition: N	OE/CC	NOE/CONTOUR	1	Segment:	Target Acquisition: Recorded Automatic, Point Target	quisiti get	on: Re	corde	d Auto	matic	_1	Page	4 of 7	Pages
	,							•						
	Loca-	Operator-Equipment	Perform-	Operator	Informa-		Mental	Load	Motor	$\overline{1}$	Delay Toler-	Task Criti-		
Systems	tion	E	ed by	Activity		D/N	Amt Diff	-	Amt Diff	_	_	cality	Comments	
i. Turbine Gas Tem-	Ċ,	Check limits	۵	V	QA	D	3	2	2	2	3	3		
perature Indicator			•			N	3	2	2	2	۳	8		
i . Selectable Digital	U					D								
Display	,					Z								
. Intercommunication						Ω								
System						Z				-				
a. ICS Switch	æ	Press to talkICS	ц	M	୯୬	Ω	2	2	8	2	8	4		
			3			N	2	2	8	2	8	4		
b. Microphone	æ	Coordinate aircraft position	Œ	S	QA, QT	Q	5	က	4	2	4	4		
		to service target	,			Z	9	4	4	2	4	4		
c. Earphone	Ø	Monitor ICS	В	٧	QA, QT	Ω	4	3	4	6	4	4		
					CK	N	5	3	4	8	4	4		
7. External Communica-						α								
tion Systems						Z								
a. Communication	æ					Q								
Control Panel						N								
b. Radio/ICS Rocker	щ					D								
Switch						N								
c. Remote/Transmit-	ρ.					Q								
ter Selection Switch						N								
			Í		•									

MANAGE TRANSPORTED FOR CONTRACTOR TO SERVICE

Figure B-1. (cont.)

机

	Visibility Condition: D	D-N VMC	Phase:	Target Servicing				Summ	Summary No.:	ı	3. 1. а.	- }	Aircraft:	ı	A11-64		ı
	Flight Condition: N	OE/CC	NOE/CONTOUR	1	Segment:	Target Acquisition: Recorded Automatic, Point Target	quisiti get	ion: Re	corde	d Aute	omatic	اء.	Page	c ₂	ě	7 B	Pages
	Svstems	Loca- tion	Operator-Equipment Functional Interaction	Perform-	Operator	Informa- tion Type	Z/0	Mental Amt Diff	Load tal	Amt Diff		Delay Toler-	Task Criti-	Comments	r to to		
	-/ AM Badio	a	Monitor air-to-air	٥	M.A	QA, CK	_	3	4	4	+	8	+				
•				•			z	3	4	4	2	3	8				
•	c. VHE/AM/EM Ba-	a	Monitors FM, TR with	a	M, A	QA, CK	Ω	3	4	4	2	2	2				
•	dio/Homing #1		ground				z	3	4	4	2	2	2				
	f. VHE/AM/EM	ر					a										
•	Radio #2	,					z										
47	g. Voice Security	ر					Ω										
•		,					z										
	h, Voice Security	Ω,					Q										
•	VIIF/FM						z										
	1. IFF Transponder	<u>a</u>					Ω										
•							z										
	8. Navigation System						D										
,							z							•			
	a, Direction Finder	ρ,					a										
•	Controls						z										
	b. Doppler Navigation	<u>ن</u>	Monitor heading and course	· ·	^	VÖ	Ω	4	4	4	2	3	3				
•	Control Panel		Jeviation	,			z	4	4	4	2	3	3				
	c. Electronic Attitude			,			Ω										
•	Director Controls						Z										
				!													

Ž

Figure B-1. (cont.)

Visibility Condition: D	D-N VMC	Phase:	Target Servicing	pt.		V)	Summary No.:	y No.	3.1.a.1	[:]	Aircra	Aircraft: AII-64
Flight Condition:	OE/CO	NOE/CONTOUR	1	Segment:	Target Acquisition: Recorded Automatic. Point Target	nisition t	: Recor	ded Au	tomatic	.]	Page	6 of 7 Pages
Systems	Loca- tion	Operator-Equipment Functional Interaction	Perform- ed by	Operator Activity	Informa- tion Type	D/N	Lo Mental Amt Diff		Motor Amt Diff	Delay Toler-	Task Criti-	Comments
d. Hertzontal Situa- tion Control Panel	C.					ΩΖ						
e. Heading/Attitude	ď					Ω	$\left \cdot \right $		-			
Reference Control						z	1		_			
f. Radar Altimeter	Ľ					Ω						
Control						z			_			
9. Survivability Devices						Q						
R						2	_	L.	L			
a. Radar/IR Counter-	C.					Ω	_	_	_			
measure Control						Z		<u> </u>	_			
b. Radar Warning	۵.	Monitor	d	Λ	CK	О	3	3	2	3	3	
Display						N	က	3	2	3	3	
C. Radar Warning	С,					Q						
Control						z		_	_			
						Ω	-	_				
Equipment						z						
and Display Sight	m	Monitor symbology and	C.	Μ, ۷	QA, QT	D	4	4 4	4	3	3	NightPNVS
System		sensor display			СK	z	9	6 5	2	5	5	
b. Heads Out Display	U					Q			_			
						z		_				

Figure B-1. (cont.)

Visibility Condition;	D-N VMC	Phase:	Target Servicing				Summ	Summary No. :	۳] د	3. l. a. 1		Aircraft:	AH-64
Flight Condition:	NOE/C	NOE/CONTOUR	1	Segment:	Target Acquisition: Recorded Automatic, Point Target	uisitic	n: Re	corded	Autor	natic,	•	Page 7	of 7 Pages
Svstems	Loca- tion	Operator-Equipment Functional Interaction	Perform- ed by	Operator Activity	Operator Informa- Activity tion Type	D/N	L Mental Amt Diff	- lö	Motor Amt i Diff		Delay Toler-	Task Criti-	om monto
c. Heads Down Dis-	U	Search for target	Э	M, V	QA	Ω	4	+	4		4		
play			,		CK	z	2	2	5	4	4	4	
11. Target Engagement						Q				-			
Devices						N				-			
a. Collective Switch	m					Q				-			
Box						z				-			
6 b. Data Entry Key-	U —	Recall waypoint target-set to TRGT and enter storage	۲	¥	QA, QT	Ω	4	8	₆	2	<u>س</u>	8	
board		location	,			Z	4	3	3	2	6	8	
c. Digital Message	Д					α		-		-			
Devices						Z				-			
d. Fire Control	n	Select sight and acquisition	υ	M, V	QA, QT	D	က	2	8	2	3	3	
Panel		modes				z	8	2	3	2	8	3	
e. Handgrip Left	ပ —	Adjust FOV, press UPDT	υ	M, V	QA, QT	α	3	2	3	2	23	8	
		and set IAT				Z	3	.2	3	2	2	8	
f . Handgrip Right	U	Slave TADS to waypoint target, adjust line of sight.	ပ	M	QA	D	3	3	2	2	~ ~	6	
		if necded				N	3	3	2	2	8	3	
g. Missile Control	æ					α				_			
Panel						N			r	-			
h. Rocket Control	22					Ω				-			
ואחפו						z							
				Highra	R-1 (c)	1 +000)							

All and the second of the second seco

Figure B-1. (cont.)

APPENDIX C

Highly Scaled Intellective Categories for Crewmembers in Each Helicopter Type

Table C-1

Most Highly Scaled Intellective Categories
Involved in Functions of AHIP Helicopter Pilots

Fu	nction	Intellective Category	Load
1.	Control flight with cyclic, collective, pedals	Cognition of figural relations Cognition of symbolic units Cognition of symbolic classes	5. 2 6. 0 6. 0
3.	Environmental orientation	Cognition of figural classes Evaluation of figural relations Evaluation of figural classes Cognition of figural relations	12* 16 8.5* 8.5*
4.	Use pilot's multi- function/displays controls	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	3.3 2.4 2.6
5.	Use CPO's multi- function displays/ controls/maps	Evaluation of symbolic implications Evaluation of figural relations Cognition of symbolic classes	8. 0 3. 0 6. 0
7.	Intracrew communication	Evaluation of figural classes Convergent production of symbolic units Convergent production of symbolic implications Convergent production of figural implications	15. 0 12. 0 12. 0 12. 0
8.	External communication	Memory of semantic classes Memory of semantic units	3.5 6.0
9.	Uses survivability devices	Cognition of figural classes Convergent production of symbolic relations Cognition of symbolic classes Convergent production of symbolic implications	12.0 6.0 3.0 3.0
11.	Use MLMS controls	Evaluation of symbolic classes Cognition of symbolic classes Cognition of figural classes	12.0 2.0 4.0

^{*}Poor visibility data

Table C-2

Most Highly Scaled Intellective Categories
Involved in Functions of AHIP Helicopter Observers

Fu	nction	Intellective Category	Load
2.	Read/monitor secondary flight instruments	Convergent production of symbolic classes Evaluation of symbolic classes	5.25 5.25
3.	Environmental orientation	Evaluation of symbolic classes Evaluation of figural classes Evaluation of symbolic transformations Cognition of figural classes Convergent production of figural transformations	12.0* 12.0* 12.0* 12.0* 12.0*
5.	Use CPO's multi- functional displays, controls, maps	Evaluation of figural classes Convergent production of symbolic units Evaluation of symbolic units	12.3 12.0 9.5
6.	Monitor/read system instruments	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	4.0 3.7 1.9
7.	Intracrew communication	Convergent production of symbolic implications Cognition of symbolic relations Evaluation of figural units Evaluation of semantic classes	12.3 12.0 12.0 12.0
8.	External communication	Evaluation of figural relations Evaluation of semantic units Convergent production of symbolic implications	12.0 12.0 10.1

^{*}Poor visibility data

Table C-3

Most Highly Scaled Intellective Categories

Involved in Functions of AH-64 Helicopter Pilots

Function Intellective Category Load 9.0 1. Control flight Evaluation of symbolic relations with cyclic, Cognition of symbolic classes 6.0 collective, pedals Cognition of figural relations 4.7 2. Read/monitor Cognition of symbolic units 4.0 flight, caution Evaluation of symbolic classes 2.9 Evaluation of symbolic relations & warning 2.0 instruments 3. Environmental Evaluation of figural relations 16.0 orientation Cognition of figural classes 12.7* Convergent production of figural classes 13.0* 4.7 4. Use integrated Cognition of symbolic units flight, navigation Evaluation of symbolic relations 3.5 displays/maps Evaluation of symbolic classes 2.8 5. Monitor/read Cognition of symbolic units 4.0 systems Evaluation of symbolic classes 2.9 instruments Evaluation of symbolic relations 2.0 16.0 6. Intracrew Evaluation of figural classes Convergent production of symbolic implications communication 13.3 Cognition of figural classes 12.0 Convergent production of figural implications 12.0 7. External Cognition of semantic classes 6.0 communication Convergent production of semantic classes 6.0 Evaluation of symbolic units 6.0 8. Use navigation Memory of symbolic units 12.0 system to fly a Cognition of symbolic relations 10.0 course Memory of semantic units 9.0 12.0 9. Use survivability Cognition of figural classes devices Convergent production of symbolic relations 6.0 3.0 Cognition of symbolic classes

Convergent production of symbolic implications

3.0

Table C-3 (cont.)

Fu	nction	Intellective Category	Load
10.	Use TADS/PNVS displays for threat identification	Cognition of symbolic units Evaluation of figural classes Evaluation of symbolic classes Evaluation of symbolic relations Evaluation of symbolic implications	4.0 2.0 2.0 2.0 2.0
11.	Use devices & controls to select/engage target	Evaluation of symbolic classes Evaluation of figural relations Convergent production of symbolic implications	12.0 12.0 8.0

^{*}Poor visibility data

Table C-4

Most Highly Scaled Intellective Categories
Involved in Functions of AH-64 Helicopter Copilots

Fur	nction	Intelligence Category	Load
2.	Read/monitor flight caution & warning instruments	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	4.0 2.0 2.0
3.	Environmental orientation	Evaluation of symbolic classes Evaluation of figural classes Convergent production of figural transformations	12.0* 12.0* 12.0*
4.	Use integrated flight navigation displays, maps	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	4.0 3.0 3.0
5.	Monitor/read systems instruments	Cognition of symbolic units Evaluation of symbolic relations Evaluation of symbolic classes	5.4 3.4 2.9
6.	Intracrew communication	Cognition of semantic classes Convergent production of symbolic implications Cognition of symbolic relations Evaluation of symbolic relations Evaluation of semantic classes	16.0 12.3 12.0 12.0 12.0
7.	External communication	Convergent production of symbolic classes Convergent production of semantic implications Cognition of symbolic classes	16.0 8.0 8.0
8.	Use navigation system to fly a course	Cognition of symbolic relations Convergent production of symbolic transformations Evaluation of symbolic implications	12.0 12.0 10.0
10.	Use TADS/PNVS displays	Convergent production of symbolic units Evaluation of figural classes Evaluation of figural relations Evaluation of symbolic transformations	12.0 9.0 9.0 9.0
11.	Use devices & controls to select/ engage target	Evaluation of figural classes Evaluation of symbolic classes Cognition of figural classes	12.0 12.0 12.0

Table C-5

Most Highly Scaled Intellective Categories Involved in Functions of AH-1S Helicopter Pilots

Fu	nction	Intellective Category	Load
1.	Control flight with cyclic, collective, pedals	Evaluation of symbolic relations Cognition of figural relations Cognition of figural relations	9.0 10.5* 4.7
2.	Read/monitor primary flight instruments	Evaluation of symbolic relations Evaluation of symbolic classes Cognition of symbolic units	2.0 2.0 4.0
3.	Environmental orientation	Evaluation of figural relations Evaluation of symbolic transformations Convergent production of figural classes	12.0* 12.0* 12.0*
4.	Use integrated flight/navigation displays/maps	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	4.6 3.2 3.25
5.	Read/monitor caution, warning & systems instruments	Cognition of symbolic units Evaluation of symbolic classes Evaluation of symbolic relations	5.3 3.6 3.3
6.	Intracrew communications	Convergent production of figural implications Evaluation of figural classes Cognition of figural classes	25.0* 20.33* 18.0*
7.	External communication	Cognition of semantic classes Convergent production of semantic classes Evaluation of semantic classes	6.0 6.0 4.5
8.	Use navigation system to fly a course	Evaluation of symbolic units Convergent production of symbolic implications Cognition of symbolic classes Memory of symbolic classes Evaluation of symbolic classes	7.5 6.5 6.0 6.0
9,	Use survivability devices	Cognition of figural classes Convergent production of symbolic units Cognition of figural classes	20.0* 16.0 12.0

Table C-5 (cont.)

Function		Intellective Category	Load
10.	Use visual sighting devices for threat	Evaluation of figural classes Evaluation of symbolic classes Evaluation of figural classes	25.0* 15.0 12.0
11.	Use controls & devices to sense, engage target	Evaluation of symbolic relations Evaluation of symbolic relations Evaluation of symbolic classes	25.0* 16.0 16.0

^{*}Poor visibility data

Table C-6

Most Highly Scaled Intellective Categories Involved in Functions of AH-1S Helicopter Copilots

Function Intellective Category		Load	
2.	Read/monitor primary flight instruments	Evaluation of symbolic relations Evaluation of symbolic classes Cognition of symbolic units	2.0 2.0 4.0
3.	Environmental orientation	Evaluation of figural classes Evaluation of symbolic classes Convergent production of figural transformations	12.0* 14.0* 12.0*
4.	Use integrated flight/ navigation displays/ maps	Evaluation of symbolic relations Evaluation of symbolic classes Cognition of symbolic units	3.0 3.0 4.0
6.	Intracrew communications	Convergent production of symbolic implications Evaluation of semantic classes Convergent production of symbolic classes Evaluation of figural units Cognition of semantic classes	20.0* 19.0* 16.0* 16.0* 16.0
7.	External communication	Convergent production of symbolic classes Convergent production of symbolic classes Evaluation of semantic classes	25.0* 16.0 10.0
8.	Use navigation system to fly a course	Evaluation of symbolic transformations Convergent production of symbolic transformations Evaluation of symbolic implications	16.0* 12.0 10.0
10.	Use visual sighting devices for threat	Cognition of symbolic units Evaluation of symbolic classes Evaluation of figural classes	25.0* 25.0* 25.0*
11.	Use controls & devices to sense, engage target	Evaluation of symbolic classes Evaluation of symbolic classes Evaluation of figural classes	16.0* 5.3 6.0

^{*}Poor visibility data